

SAFETY DATA SHEET

R-407C

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: FLORON 407C

TRADE NAMES/SYNONYMS F-407C, R-407C

Product Use: Refrigerant Gas

Manufacturers: SRF Ltd. Chemicals Business
V&PO: JHIWANA, Tehsil. TIJARA, Dist. - ALWAR,
RAJASTHAN, INDIA
Pin Code-301018

EMERGENCY CONTACT: (24 Hours/Day, 7 Days/Week)
M/S. SRF Limited
+91 – (01493) 245163, 400

2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Classification : Gases under pressure, Liquefied gas

GHS label elements

Hazard Pictogram



Signal word : WARNING

Hazard pictogram code : **GHS04**

Signal word : Warning

Hazard Statement : **H280:** Contains gas under pressure, may explode if heated

Symbol : Gas Cylinder

PRECAUTIONARY STATEMENT

STORAGE : **P410+P403:** Protect from sunlight, store in a well ventilated place

EMERGENCY OVERVIEW: Colorless, volatile liquid with ethereal and faint sweetish odor. Non-flammable material. Overexposure may cause dizziness and loss of concentration.

SRF LIMITED

Block-C, Sector-45
Gurgaon 122 003
Haryana, India
Tel: +91-124-4354400
Fax: +91-124-4354500
Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
DLF Galleria, Mayur Place, Noida
Link Road, Mayur Vihar Phase I
Extn, Delhi- 110 091, India

At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250°C), decomposition products may include Hydrofluoric Acid (HF) and carbonyl halides.

POTENTIAL HEALTH HAZARDS

SKIN: Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

EYES: Liquid contact can cause severe irritation and frostbite. Mist may irritate.

INHALATION: F-407C is low in acute toxicity in animals. When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

INGESTION: Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

DELAYED EFFECTS: None known.

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

<u>INGREDIENT NAME</u>	<u>NTP STATUS</u> <u>OSHA LIST</u>	<u>IARC STATUS</u>
------------------------	---------------------------------------	--------------------

No ingredients listed in this section

3. COMPOSITION, INFORMATION ON INGREDIENTS

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>WEIGHT %</u>
Difluoromethane (F-32)	75-10-5	23
Pentafluoroethane (F-125)	354-33-6	25
1,1,1,2-Tetrafluoroethane (F-134a)	811-97-2	52

4. FIRST AID MEASURES

SKIN: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

SRF LIMITED

Block-C, Sector-45
Gurgaon 122 003
Haryana, India
Tel: +91-124-4354400
Fax: +91-124-4354500
Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
DLF Galleria, Mayur Place, Noida
Link Road, Mayur Vihar Phase I
Extn, Delhi- 110 091, India

INHALATION: Immediately remove to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention. Do not give epinephrine (adrenaline).

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

ADVICE TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT:	Gas, not applicable per DOT regulations
FLASH POINT METHOD:	Not applicable
AUTOIGNITION TEMPERATURE:	Unknown for mixture
UPPER FLAME LIMIT (volume % in air):	None*
LOWER FLAME LIMIT (volume % in air):	None*
*Based on ASHRAE Standard 34 with match ignition	
FLAME PROPAGATION RATE (solids):	Not applicable
OSHA FLAMMABILITY CLASS:	Not applicable

EXTINGUISHING MEDIA:

Use any standard agent – choose the one most appropriate for type of surrounding fire (material itself is not flammable).

UNUSUAL FIRE AND EXPLOSION HAZARDS:

R-407C is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources. Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and/or appropriate pressures).

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed.

SRF LIMITED

Block-C, Sector-45
Gurgaon 122 003
Haryana, India
Tel: +91-124-4354400
Fax: +91-124-4354500
Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
DLF Galleria, Mayur Place, Noida
Link Road, Mayur Vihar Phase I
Extn, Delhi- 110 091, India

6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR OTHER RELEASE:

(Always wear recommended personal protective equipment.) Evacuate unprotected personnel. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return until air has been tested and determined safe, including low-lying areas.

7. HANDLING AND STORAGE

NORMAL HANDLING:

Always wear recommended personal protective equipment.) Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders. F-407C should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

STORAGE RECOMMENDATIONS:

Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:

Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with the liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

EYE PROTECTION:

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

RESPIRATORY PROTECTION:

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH- approved breathing apparatus or supplied

SRF LIMITED

Block-C, Sector-45
Gurgaon 122 003
Haryana, India
Tel: +91-124-4354400
Fax: +91-124-4354500
Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
DLF Galleria, Mayur Place, Noida
Link Road, Mayur Vihar Phase I
Extn, Delhi- 110 091, India

air respirator. For escape: use the former or a NIOSH-approved gas mask with organic vapor canister.

ADDITIONAL RECOMMENDATIONS:

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose-level warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick-drench shower facilities at convenient locations. For tank cleaning operations, see OSHA regulations, 29 CFR 1910.132 and 29 CFR 1910.133.

EXPOSURE GUIDELINES

<u>INGREDIENT NAME</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT</u>
Difluoromethane	None	None	*1000 ppm TWA (8hr)
Pentafluoroethane	None	None	*1000 ppm TWA (8hr)
1,1,1,2-Tetrafluoroethane	None	None	*1000 ppm TWA (8hr)

* = Workplace Environmental Exposure Level (AIHA)

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Hydrogen Fluoride: ACGIH TLV: 3 ppm ceiling

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear, colorless liquid and vapor
PHYSICAL STATE:	Gas at ambient temperatures
MOLECULAR WEIGHT:	86.2
CHEMICAL FORMULA:	CH ₂ F ₂ , CF ₃ CHF ₂ , CH ₂ FCF ₃
ODOR:	Faint ethereal odor
SPECIFIC GRAVITY (water = 1.0):	1.16 @ 21.1°C (70°F)
SOLUBILITY IN WATER (weight %):	Unknown
pH:	Neutral
BOILING POINT:	-43°C (-45.4°F)
FREEZING POINT:	Not Determined
VAPOR PRESSURE:	156.2 psia @ 70°F 356.7 psia @ 130°F
VAPOR DENSITY (air = 1.0):	3.0
EVAPORATION RATE:	>1 COMPARED TO: CC14 = 1

SRF LIMITED

Block-C, Sector-45
Gurgaon 122 003
Haryana, India
Tel: +91-124-4354400
Fax: +91-124-4354500
Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
DLF Galleria, Mayur Place, Noida
Link Road, Mayur Vihar Phase I
Extn, Delhi- 110 091, India

% VOLATILES: 100
 FLASH POINT: Not applicable
 (Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

The product is stable.

Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

INCOMPATIBILITIES:

(Under specific conditions: e.g. very high temperatures and/or appropriate pressures) – Freshly abraded aluminum surfaces

(may cause strong exothermic reaction). Chemically active metals: potassium, calcium, powdered aluminum, magnesium and zinc.

HAZARDOUS DECOMPOSITION PRODUCTS:

Halogens, halogen acids and possibly carbonyl halides.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

IMMEDIATE (ACUTE) EFFECTS:

F-32: LC₅₀ : 4 hr. (rat) - 520,000 ppm / Cardiac Sensitization threshold (dog) 350,000 ppm
 F-125: LC₅₀ : 4 hr. (rat) - > 800,000 ppm / Cardiac Sensitization threshold (dog) 75,000 ppm
 F-134a: LC₅₀: 4 hr. (rat) - > 500,000 ppm / Cardiac Sensitization threshold (dog) > 80,000 ppm

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

F-32: Teratogenic NOEL (rat and rabbit) – 50,000 ppm
 Subchronic inhalation (rat) NOEL – 50,000 ppm
 F-125: Teratogenic NOEL (rat and rabbit) – 50,000 ppm
 Subchronic inhalation (rat) NOEL - ≥ 50,000 ppm
 Chronic NOEL – 10,000 ppm
 F-134a: Teratogenic NOEL (rat and rabbit) – 40,000 ppm

SRF LIMITED

Block-C, Sector-45
 Gurgaon 122 003
 Haryana, India
 Tel: +91-124-4354400
 Fax: +91-124-4354500
 Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
 DLF Galleria, Mayur Place, Noida
 Link Road, Mayur Vihar Phase I
 Extn, Delhi- 110 091, India

Subchronic inhalation (rat)
 NOEL – 50,000 ppm
 Chronic NOEL – 10,000 ppm

OTHER DATA:

F-32, F-125, F-134a: Not active in four genetic studies

12. ECOLOGICAL INFORMATION

Degradability (BOD): R-407 C/ F-407C is a gas at room temperature; therefore, it is unlikely to remain in water.

Octanol Water Partition Coefficient: Unknown for mixture

Environmental Information: The gas (F-407 A) is having **Zero ODP** (Ozone Depleting Potential)

13. DISPOSAL CONSIDERATIONS

RCRA

Is the unused product a RCRA hazardous waste if discarded? Not a hazardous waste.
If yes, the RCRA ID number is: Not applicable.

OTHER DISPOSAL CONSIDERATIONS:

Disposal must comply with federal, state, and local disposal or discharge laws. F-407C is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME: Refrigerant gas F 407C
HAZARD CLASS: 2.2
PACKING GROUP: Not applicable
ID NUMBER: UN3340



For additional information on shipping regulations affecting this material, contact the information

SRF LIMITED

Block-C, Sector-45
 Gurgaon 122 003
 Haryana, India
 Tel: +91-124-4354400
 Fax: +91-124-4354500
 Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
 DLF Galleria, Mayur Place, Noida
 Link Road, Mayur Vihar Phase I
 Extn, Delhi- 110 091, India

number found in Section 1.

15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Components listed on the TSCA inventory
OTHER TSCA ISSUES: None

SARA TITLE III / CERCLA

“Reportable Quantities” (RQs) and/or “Threshold Planning Quantities” (TPQs) exist for the following ingredients.

INGREDIENT NAMESARA / CERCLA RO (lb.).....SARA EHS TPO (lb.)

No ingredients listed in this section

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: IMMEDIATE PRESSURE

SARA 313 TOXIC CHEMICALS:

The following ingredients are SARA 313 “Toxic Chemicals”. CAS numbers and weight percent are found in Section 2.

INGREDIENT NAME

No ingredients listed in this section

COMMENT

ADDITIONAL REGULATORY INFORMATION:

F-407C is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

WARNING: Do not vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered. **Contains Pentafluoroethane (F-125), Difluoromethane (F-32), and Tetrafluoroethane (F-134a)**, greenhouse gases which may contribute to global warming.

WHMIS CLASSIFICATION (CANADA):

This product has been evaluated in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

SRF LIMITED

Block-C, Sector-45
 Gurgaon 122 003
 Haryana, India
 Tel: +91-124-4354400
 Fax: +91-124-4354500
 Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
 DLF Galleria, Mayur Place, Noida
 Link Road, Mayur Vihar Phase I
 Extn, Delhi- 110 091, India

FOREIGN INVENTORY STATUS:
EU – EINECS # 2065578 – F-125
2008394 – F-32
223770 – F-134a

16. OTHER INFORMATION

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.

SRF LIMITED

Block-C, Sector-45
Gurgaon 122 003
Haryana, India
Tel: +91-124-4354400
Fax: +91-124-4354500
Website: www.srf.com

Regd. Office:

Unit No. 236 & 237, 2nd Floor,
DLF Galleria, Mayur Place, Noida
Link Road, Mayur Vihar Phase I
Extn, Delhi- 110 091, India